



Auslaufventil, PN 16

- Werkstoff: Rotguss, Chromnickelstahl, EPDM, Metall
- Bestehend aus: integriertem Rohrbelüfter, Handrad
- *verchromt

	GN (inch)	DN (mm)	JRG Code	GF Code	SP	Gewicht (kg)
	½	15	7015.240	355 624 418	1	0.560
	¾	20	7015.320	355 624 433	1	0.590
*	½	15	7015.241	355 624 422	1	0.560
*	¾	20	7015.321	355 624 437	1	0.590

	GN (inch)	DN (mm)	d1 R (inch)	d2 G (inch)	d3 G (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	□ (mm)	□ (mm)
	½	15	½	¾	½	50	71	36	22	94	28	6
	¾	20	¾	1	½	50	71	39	25	93	28	6
*	½	15	½	¾	½	50	71	36	25	93	28	6
*	¾	20	¾	1	½	50	71	39	22	94	28	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>